

ACCORDING TO ANNEX №1 OF REGULATION № RD - 02-20-1/05.02.2015

DECLARATION OF THE CHARACTERISTICS OF CONSTRUCTION PRODUCTS № BTT – 005 – 08 – 16

1. Unique identification code of the product type:

BOROLEX SATIN

2. National requirements (Order of the Minister of Regional Development and Public Works, national regulation) technical specification (national standard, Bulgarian technical approval) applicable to the construction product: **TS – BT - 005**

3. Intended use or uses of the construction product in accordance with national requirements as provided by the producer: **It is used for interior painting of cement, lime-cement, gypsum plasters and putties, concrete surfaces, plasterboard, aerated concrete, embossed and paper wallpapers, old latex coatings and others in which the requirement is to obtain a satin gloss.**

4. Name, registered trade name or registered trademark contact address of the producer and place of production:

„BORO TERACOL“Ltd., 1261 Mramor village, 10 Boro Str.

TEL. +359 2 892 39 21

FAX: +359 2 892 39 45

E-MAIL: boro_techn@boro-bg.com

5. Name and contact address of the authorized representative (where applicable):

Eng. Pavlina Petrova "Boro Teracol" Ltd. TEL. +359 2 892 3947

6. Name of person to assess compliance with national requirements (if applicable): **Not applicable**

(certificate of conformity, test / calculation (depending on the applicable)

7. Declared parameters of the characteristics of the construction product:

Characteristic	Parameter	Test method / calculation / determination
Appearance of the paint	White, homogeneous, thick mass	visually
Non - volatile substances content, at (125±2)°C/2h, in %	55 - 57	BS EN ISO 3251
Brookfield viscosity at (23 ± 0,5)°C, in mPa.s	2200 - 3500	BS ISO 2555
Dry at touch at (23 ± 2) °C and relative humidity (50 ± 5)%, in min, not more than	20	TS – BT - 005
pH value	min 8,0	with pH-meter
Density at (20±0,5)°C, in kg/l	1,25 – 1,40	BS EN ISO 2811-1
Appearance of the film	Flat, smooth, matt	visually
Fineness	fine (less than 100 microns)	BS EN 13300
Resistance to wet rubbing	class 1 - high resistant	BS EN 13300
Gloss	semi-gloss	BS EN 13300
Hiding power	class 2 (9,0-10,0) m ² /l (full hiding power)	BS EN 13300

8. The characteristics of the construction product specified in pt. 1 have the parameters corresponding to declared in accordance with pt. 7.

This declaration of the characteristics of the construction product shall be issued under the sole responsibility of the producer under pt. 4 or the authorized representative under pt. 5.

Signed for and on behalf of the producer (authorized representative):

Sofia
December, 2018

DIRECTOR:
/eng. B.Dachev/

