

DECLARATION OF PERFORMANCE



IN ACCORDANCE WITH EU CONSTRUCTION PRODUCT REGULATION (CPR) No 305 /2011

№ BT-019-07-13

1. Unique identification code of the product-type:

Gypsum adhesive

2. Type, batch or serial number or any other element allowing identification of the construction as required under Article 11(4):

Batch number: See packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For internal walls and dry rooms

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

BORO TERACOL LTD, 1261 MRAMOR VILLAGE, 10 BORO STR.

TEL. +359 2 892 39 21

FAX +359 2 892 39 45

E-MAIL **boro_tech@boro-bg.com**

5. Where applicable, name and contact address of the representative whose mandate the tasks specified in Article 12(2):

ENG.PAVLINA PETROVA BORO TERACOL LTD TEL. +359 2 892 39 47

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

SYSTEM 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
BS EN 12860

Test laboratory for construction materials – Conformity direction assessment of construction products CPD 05 – NB 1950 / 17.09.2007 in permission to Research Institute of Building Materials Ltd carried out type testing of the product and issued system3 Protocol for performed Initial type testing under system 3 and issued Test report No1046/23.10.2008. On the grounds of the test the producer marked the packaging with CE in 2008.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

NOT APPLICABLE

9. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Tensile adhesion strength	1,1 N/mm ² разрушаването е гипсовия блок	BS EN12860
Particle retained on sieve size: 0,2 mm 0,4 mm	2,8% 0%	
Setting time: start end	105 min 120 min	
Work ability	152 mm	
Content of sulphur trioxide	>30%	
Reaction to fire	Class A1	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:


Mr. Bogomil Dachev

name

Director

function

Sofia
12/2018



DECLARATION OF PERFORMANCE