

**FUGAFIX****Silicone impregnator for grouts, antiseptic****FOR INTERNAL AND EXTERNAL APPLICATION**

<b>PURPOSE:</b>	
For impregnation of new and refreshment of old grouts, covered with ceramic tile floors and walls. With antiseptic action. Do not mix with other similar products, and application at temperatures lower than 5°C and higher than 35°C.	
<b>QUALITIES:</b>	
<ul style="list-style-type: none"><li>- Hydrophobizing in depth of grouts, emphasizing color and making it pure</li><li>- Protects them from dirt and facilitates their cleaning</li><li>- Forms a colorless coating and does not change the color of grout</li><li>- Formed in depth resistant to moisture barrier</li><li>- Fast drying</li><li>- Good application behavior. Minor losses application</li><li>- Correspond to the Bulgarian and European legislation</li></ul>	
<b>CLASSIFICATION:</b>	
The maximum VOC content for this product (cat.: A / a) is 30 g/l	
<b>TECHNICAL DATA OF THE PRODUCT:</b>	
<b>Appearance:</b> (visually)	Homogeneous mass.
<b>Density:</b> (BS EN ISO 2811-1)	1,00-1,05 kg/l
<b>Drying:</b> at (23 ± 0,5)°C, 65% H.R	air dry to the touch 20-30 min
<b>CONSUMPTION RATE:</b>	
10 - 30 ml/m <sup>2</sup> , tiled surface depending on the size of the tiles and width of grouts.	
<b>SHELF LIFE:</b>	
24 months from the production date in fabrically closed packages.	
<b>PACKAGING:</b>	
Plastic packages with a net weight of 0.5 l; 1.0 l. It is possible to use and other packaging after prior agreement with the client.	
<b>COLOUR:</b>	
Milky white. It forms a transparent film.	
<b>STORAGE:</b>	
Store in covered and dry warehouses at 5 <sup>0</sup> C to 40 <sup>0</sup> C, protect from direct sunlight.	
<b>Warning! Protect from freezing during storage and transport!</b>	
<b>P102</b> - Keep out of reach of children.	
<b>P262</b> - Avoid contact with eyes, skin or clothing.	
<b>P301 + P310</b> - In swallowed immediately call a POISON CENTER or doctor.	
<b>P273</b> - Avoid release to the environment.	
<b>DILUENT:</b>	
Water	
<b>PREPARATION OF THE BASE:</b>	

The old grouts need to be cleared of pollution. At damaged grouts need to be filled again with grout mixture. Before applying the impregnator grouts must be dried.			
<b>SUITABLE BASES:</b>			
- Grouting surfaces			
<b>UNSUITABLE BASES:</b>			
- Glass surfaces			
- Plastic surfaces			
<b>APPLICATION INSTRUMENTS:</b>			
- Brush			
<b>CLEANING OF THE INSTRUMENTS:</b>			
With water before they are dry.			
<b>APPLICATION CONDITIONS:</b>			
- It is applied at temperatures not lower than 5 °C and not higher than 35 °C.			
- Do not mix with other similar products.			
<b>WAY OF WORKING:</b>			
To stir before use. Apply carefully with a thin brush along the length of the joint in several layers to saturation. The application is carried out only on well dried grout. Treated grouts to keep from water 24 hours after application. Dirty tiles are wiped with a wet towel before the retainer is dried.			
<b>APPLICATION SYSTEM:</b>			
<b>Base</b>	<b>Priming</b>	<b>Intermediate layer</b>	<b>Finishing layer</b>
- Grouting surfaces	FUGAFIX Silicone impregnator	-	FUGAFIX Silicone impregnator
<b>HYGIENE AND SAFE WORK:</b>			
The product is not classified as dangerous. If necessary, refer to the Safety Data Sheet.			